

Customer & Trailer Info

Name	Year	
Address	Make	
	Model	
Phone	Date	
Email		

Extension Info

Size	12 ″	18 ″	24"	□ 30 ″ □ 36 ″ □ 42 ″ □ 48 ″	
Model		В	C	D (OFFICE USE ONLY)	
Тор	🗌 Standard			🗌 Dome Style	
Color	🗌 White	e	🗌 Black	🗌 Grey	



Your Order Number

*All Fields Must Be Completed To Process Your Order. (928) 404-3825 2958 Sweetwater Ave, Ste. 100 Lake Havasu City, AZ 86406 Take pictures of this completed form and email to bryan@toyhaulerextensions.com

Top Dome Style Measurements



Customer & Trailer Info

Name	Year	
Address	Make	
	Model	
Phone	Date	
Email		



- Always follow Trailer Manufactures warning labels for load capacity and weight.
- Our EXTENSION KIT WEIGHT gets SUBTRACTED FROM THE TOTAL TRAILER LOAD CAPACITY.
- Improper loading can cause trailer sway and sudden loss of control.
- YOU MUST:
 - 1. Make certain weight of load plus trailer weight does not exceed trailers capacity. (GVWR- gross veichle weight rating).
 - 2. Load heavier items towards front of wheels.
 - 3. Load evenly side to side
 - 4. SECURE load to trailer.
 - 5. Close and PIN or LOCK doors.



• YOU MUST CHECK THE FOLLOWING BEFORE TOWING, AND AT ALL STOPS:

- **1. Ball correct size and property secured.**
- 2. Coupler properly secured and safety lock pin installed.
- 3. Safety chains hooked up properly.
- 4. Front half of trailer must support and be loaded with 50% of more of the total load.
- 5. Brake check, so that brakes function properly.
- 6. All lights and turn signals working.
- 7. Lug nuts tight (90 lbs. torque) min.
- 8. Tire pressure meets manufacturer's specification.
- 9. All doors and gates are secured.
- 10. Safety pins and locks are secured and checked.

DO NOT EXCEED MAXIMUM RECOMMENDED WEIGHT FOR THIS TRAILER!

I HAVE READ THE ABOVE INFORMAION

Χ_____